

CityLine




QUARTZ
LUXURY



The CityLine Series of Quartz Luxury Windows and Doors by Quaker is engineered to push the boundaries of modern engineering and bring into view the true meaning of contemporary living.

Distinct and synchronized, this designer-driven collection has been fashionably bundled to infuse flair and dimension into how you select windows and doors, melding patented proprietary technologies and bringing to life the ability to envision tomorrow, today.







CityLine Windows Size & Performance (C600, C605)

- Patented OptiCore® Technology Framing System
 - 4-1/8" Architectural Grade Aluminum Frame
 - 2-7/8" Narrow Sight Lines
 - Dual Euro-Groove Frame System
- Azo-Core Thermal Barrier System for Increased Energy Efficiency and Reduced Thermal Conductivity
- Multiple Glazing Package Options Compliment Region and Climate
- Structural Mull Availability Offers Wider and Taller Sizing Options
- Square (C600) and Bevel (C605) Stop Options for Enhanced Exterior Look
- Internal or Simulated Divided Light (SDLs) Grids Available
- High-Performance 2604 and 2605 Powder Finishes
- Optional Exterior and Interior (Two-Tone) Color Options
- Custom Color Matching and Heat Reflective Paint Options
- Easily Removable FlexScreen System

Window Sizing				
Operation	Width		Height	
	Min	Max	Min	Max
Direct Set	15"	144"	15"	144"
Casement	24"	48"	22"	96"
Casement Push-Out	24"	36"	18"	72"
Awning	24"	72"	24"	84"



Window Performance						
Operation	Rating	Structural Load (P.S.F.)	Air Infiltration	Water (P.S.F.)	U-Value	SHGC
Direct Set	AW-PG100	100	0.01	12.11	0.14 - 0.28	0.24 - 0.36
Casement	AW-PG70	70.18	0.01	12.11	0.17 - 0.28	0.19 - 0.29
Casement Push-Out	AW-100	70.18	0.01	12.11	0.17 - 0.26	0.19 - 0.29
Awning	AW-PG70	70.18	0.01	12.11	0.17 - 0.28	0.19 - 0.29

The products described above are protected by one or more patents. Please refer to www.quakerwindows.com/patent-information for more information.

CityLine C-Series Sliding Doors Size & Performance (C200S)

- Architectural Grade Aluminum Frame
 - 4-9/16" and 6-9/16" Jamb Depths
 - 4-1/2" Overall Sight Line including Frame
 - 3-3/8" Sight Lines - Narrow Panel
- Patented SolidCore™ Thermal Barrier in Doors
- Corner Key Technology for Maximum Structural Performance
- Stainless Steel Quad and Tandem Precision Bearing Roller Systems
- Butt Joint Panels & Extruded Fin
- Internal or Simulated Divided Light (SDLs) Grids Available
- High-Performance 2604 and 2605 Powder Finishes
- Optional Exterior and Interior (Two-Tone) Color Options
- Custom Color Matching and Heat Reflective Paint Options



Sliding Door Performance		
Operation / Style	Structural Rating	U-Value Range
Two Panel	R-50 / LC-50	0.26 - 0.31
Four Panel	R-50 / LC-50	0.26 - 0.31
SDL Depth (Max Profile Height)		
Exterior	7/16"	
Interior	9/16"	

Sliding Door Sizing					
Operational Style	Width		Height		Max UI
	Min	Max	Min	Max	
Two Panel	60"	168"	78"	144"	264"
Four Panel	120"	240"	78"	144"	408"
Sidelite - Narrow	12"	108"	78"	143-7/8"	191"
Sidelite - Fixed Panel Set	24"	108"	78"	144"	191"
Transom	12"	120"	12"	108"	191"

The products described above are protected by one or more patents. Please refer to www.quakerwindows.com/patent-information for more information.



CityLine C-Series Swing Doors Size & Performance (C200I, C200O)

- Architectural Grade Aluminum Frame
 - 4-9/16" and 6-9/16" Jamb Depths
 - 4-1/2" Overall Sight Line including Frame
 - 3-3/8" Sight Lines - Narrow Panel
- Patented SolidCore™ Thermal Barrier in Doors
- Corner Key Technology for Maximum Structural Performance
- Available as Inswing (C200I) or Outswing (C200O)
- Adjustable Butt Hinges offer Multi-Directional Adjustment
- Standard, ADA, or No Sill Options
- Butt Joint Panels & Extruded Fin
- Wide and Narrow Panel Options
- Internal or Simulated Divided Light (SDLs) Grids Available
- High-Performance 2604 and 2605 Powder Finishes
- Optional Exterior and Interior (Two-Tone) Color Options
- Custom Color Matching and Heat Reflective Paint Options

Swing Door Performance		
Operation / Style	Structural Rating	U-Value Range
Single Panel	R-50 / LC-50	0.27 - 0.31
Two Panel - French	R-50 / LC-50	0.27 - 0.31
SDL Depth (Max Profile Height)		
Exterior	7/16"	
Interior	9/16"	



Swing Door Sizing					
Operational Style	Width		Height		Max UI
	Min	Max	Min	Max	
Single Panel	24"	48"	78"	144"	180"
Two Panel - French	48"	96"	78"	144"	216"
Sidelite - Narrow	15"	108"	78"	143-7/8"	191"
Sidelite - Fixed Panel Set	24"	108"	78"	144"	191"
Transom	12"	120"	12"	108"	191"

The products described above are protected by one or more patents. Please refer to www.quakerwindows.com/patent-information for more information.



CityLine M-Series Multislide Doors Size & Performance (M2055, M2065, M2075)

- Architectural Grade Aluminum Frame
 - 3" Sight Lines - Vertical Stile
 - 4" Sight Line Vertical Stile with Frame
 - 4-1/2" Sight Line - Bottom Rail
 - 5-1/8" Overall Sight Line including Sill
- Thermally Broken Aluminum Frame and Panels
- Azon™ Polyurethane Thermal Barrier in Frame
- Patented SolidCore™ Thermal Barrier in Doors
- Corner Key Frame Technology for Maximum Structure Performance
- Butt Joint Panels
- Stainless Steel Quad Precision Bearing Roller System
- Removable / Replaceable Sill
- Integrated Sill Pan acts as a Starter Strip
- Integral Extruded Nail Fin (Optional)
- High-Performance 2604 and 2605 Powder and Class 1 Anodized Finishes
- Custom Color Matching and Heat Reflective Paint Options

Grid Options	
Exterior Grid Max Height	Interior Grid Max Height
1/8"	1/8"

Performance	
Structural	Thermal
R - 15	0.34 - 0.39

Sill Options
Standard - 1-3/8" (M2055)
1" Flush Sill (No Leg) (M2065)
Flush (Staggered) Sill Flooring (M2075)

Sizing					
Operation	Width		Height		Max UI
	Min	Max	Min	Max	
Panel	24"	84"	34"	144"	204"



Panel Configurations				
2 Panel	3 Panel	4 Panel	5 Panel	6 Panel
One Direction Pocketing	One Direction Pocketing	One Direction Pocketing Bi-Parting	One Direction Pocketing	One Direction Pocketing Bi-Parting

The products described above are protected by one or more patents. Please refer to www.quakerwindows.com/patent-information for more information.

Glazing Packages Options

Glazing Package Options				
Glazing Package	U-Value	SHGC	VT	CR
Energy Enhanced	Lower	Lower	Lower	High
Energy North	Lower	Moderate	Highest	High
Energy Basic	Moderate	Low	Higher	Highest
Energy Plus	Lowest	Low	Higher	Higher
Energy 3S	Low	Lower	Moderate	Highest
Energy Max	Lower	Lower	Moderate	Higher
Energy 4S	Low	Lowest	Moderate	Highest
Energy 4S+	Lower	Lowest	Moderate	Higher
Triple Pane	Lowest	Lowest	High	Higher

- **U-Value:** Represents the heat flow through a window and is measures in BTU/hr-ft². The lower the rating the better the reduction in heat loss.
- **Solar Heat Gain (SHGC):** Is used to measure the amount of radiated heat entering a building. The lower the rating, the better the glazing package is in preventing solar gain.
- **Visible Transmittance (VT):** Measures the amount of visible light transmitted through a window.
- **Condensation Resistance (CR):** Measures how well a window resists condensation on its interior surface. The higher the rating, the better the glazing package is able to resist condensation.

Comparative Glazing Packages

Comparative Glazing Packages	STC	OITC
Single Pane Window	20	19
1" (25.5 mm) 2-Pane IG Casement	32	28
1" (25.5 mm) 2-Pane Laminated IG Casement	35	31
1.375" (34.6 mm) 3-Pane Laminated IG Casement	38	33
Other Glass Configurations Available Upon Request		

- **STC (Sound Transmission Class):** is used to calculate the results of soundproofing between rooms or through walls. It is a measurement of decibel reduction. The STC Frequency Scale ranges from 125 Hz to 4000 Hz. The higher the number, the better the product in dampening ambient sound.
- **OITC (Outside Inside Transmission Class):** This rates the transfer of sound between an outdoor space and an indoor space. OITC has a frequency scale between 80 Hz and 4000 Hz and is used for calculating sound controls against low frequency exterior sounds. The higher the number, the better the product is in dampening sound.





The Innovative Difference

A natural blending of proprietary technologies have formed the base properties that make up the CityLine Series Door System.

From the Azon® Polyurethane Foam to Azo-Brading and the addition of SolidCore™ infused panels, the CityLine Doors have been built to maximize Structural and Thermal Performance while maintaining the torsion, deflection and sheer strength properties garnered towards industry tested AW-rated commercial products.




Unique to the market, Quaker's patented SolidCore™ Thermal Barrier System integrates an Azo-Core high-density foam that acts as insulator against the natural conductivity of heat and cold, allowing for superior energy performance and product integrity regardless of size or operational style.



Effortless Performance

Engineered for the extremes, CityLine Windows were designed with Comfort in Mind. From the cold winds of the Northeast seaboard to the heat of the Southwest deserts, CityLine defines the standards on how modern day energy performance is measured.

Offered with a series of Energy-Enhanced Glass Packages, each window and door has been equipped for year-round maintenance-free versatility, a unique quality found within the Quartz Luxury Portfolio.



A. Azo-Core Thermal Barrier System with MLP™ technology utilizes a polyurethane foam that has been designed to create greater thermal performance throughout your entire home. Meets the stringent Energy Star Standards across all 50 states.

B. Cardinal Neat+ Glass is constructed to naturally decompose Greenhouse pollutants and stay cleaner longer.

C. Glass units incorporate Super Spacer, a superior condensation reducing seal that optimizes home energy efficiencies.





Technology to the Core

Originally designed for modern commercial construction applications, CityLine Windows offer the unique blending of advanced architectural engineering intertwined with a contemporary flair.

Infusing OptiCore®, a proprietary patented technology, Quaker has formed an engineering base that offers industry leading Structural, Thermal and Sound Performance, pushing the envelope of modern design and shaping the future of contemporary home construction.



A. Architecturally-enhanced 4-1/4" Aluminum Frame offers greater Structural Strength and Superior Performance regardless of climate or location.


B. Sealant-Injected Double Corner Key Construction offers improved structural integrity across the entire window frame regardless of size or shape.

C. 2-7/8" Sight Lines with Straight or Beveled Glazing Stops offer Larger Openings and Wider Views.

Solids, Textures and Resembles Metallics

Natural Tones


A blending of stepped contrasts and subtle shades.



Satin Creme



New Bone White



Oyster White



Beige



Sandstone



Beige Grey



Toffee



Earthtone



Patina Green



Moss Green



New Dark Bronze

Resembles Metallics

A modern and consistent interpretation of anodized finishes.



Clear
Anodized



Champagne
Light Range



Champagne
Dark Range



Light
Bronze



Dark Bronze
Light Range



Dark Bronze
Dark Range




Black
Anodized

Monotones

Illuminating the neutral spectrum of color saturation and hue.



White



Sky White II



Polar White



Agate Grey



Slate Grey



Telegrey I



Dark Bronze



Gloss Black



Black



Black
Heat Reflective



Dark Bronze
Heat Reflective

Historic Shades

Deepened colors that draw from the classic designs.



Teal



Interstate Blue



Holly Green



Redwood



Burgundy



Chestnut

Textures

Mixed to create visual depth and dimension on window and door surfaces.



Textured
Black



Textured
Dark Bronze



Textured
Dark Gray



Textured Dark
Espresso



Textured
Dark Espresso
Heat Reflective



Textured Black
Heat Reflective



Textured
Dark Bronze
Heat Reflective

All CityLine products can be finished with different colors inside and out,
in addition to having custom color matching capabilities.


Actual product color could vary from samples shown due to variances in print and production manufacturing processes.

Hardware Colors and Finishes

Endearing colors, chosen to enhance and frame our thoughts and visions.

CityLine Hardware


Available Hardware colors across the CityLine Product Line.



CityLine Door Configurations


Sliding

Constructed using both a fixed and operating door panel that slides inside a framed track.




Swing

Available in inswing or outswing. Door is hinged and pivots from the side.



Multislide

This system utilizes multiple panels that slide and stack to one side of the frames openings.



Photography courtesy of Berk Walters Homes and Crabtree Homes, LLC.

CityLine Window Configurations


Picture

A fixed-pane window that is available in nearly any shape or size.




Casement

Swinging outward, this window pivots from the side. Available with Roto or Push-Out hardware.




Awning

A window that pivots from the top and swings open at the bottom.



Corner

A uniquely designed picture window that angles back at 90° to wrap around a home's corner.





Quaker Window Products
504 U.S. Hwy 63 South
Freeburg, MO 65035
(800) 347-0438
www.quakerwindows.com



To learn more about
Quartz Luxury, scan here:



QTZ-CL BRCHR 0525