



TimberLine W-Series Doors (W200)

TimberLine W-Series Doors have been designed to open and elevate the visual appeal of your home's natural elegance and span the divide between the outside and inside.

By infusing an architectural aluminum frame with a natural wood pine interior, the W-Series Collection offers the chance to customize your living space and visually share the timeless comfort seen throughout the broad spectrum of modern home design.



Available in Swing or Sliding operational styles along with sidelites, transoms and multiple mulling configurations.

This innovative collection incorporates Quaker's patented SolidCore™ Technology. By integrating Azo-Core high density foam into the door panels, a blend of superior energy performance and structural strength enhances the natural charm of your home's unique style regardless of region or climate.



TimberLine W-Series Swing Door Highlights, Performance and Operational Styles

- Architectural Grade Aluminum Frame
 - 5-5/8" Frame Depth
 - 4-9/16" and 6-9/16" Jamb Depths
- Thermally Broken Aluminum Frame and Patented SolidCore™ Thermal Barrier in Doors
- Corner Key Technology for Maximum Structural Performance
- Available as Inswing (W200I) or Outswing (W200O)
- Adjustable Butt Hinges offer Multi-Directional Adjustment
- Standard, ADA, or No Sill Options
- Butt Joint Panels & Extruded Fin
- Wide and Narrow Panel Options
- Internal or Simulated Divided Light (SDLs) Grids Available
- Pine Interior
- High-Performance 2604 and 2605 Powder Finishes
- Custom Color Matching and Heat Reflective Paint Options

Swing Door Sizing (W200I / W200O)					
Operation	Width		Height		Max UI
	Min	Max	Min	Max	
Single Panel	24"	48"	78"	144"	180"
Two Panel - French	48"	96"	78"	144"	216"
Sidelight - Narrow	15"	108"	78"	143-7/8"	191"
Sidelight - Fixed Panel Set	24"	108"	78"	144"	191"
Transom	12"	120"	12"	108"	191"

Swing Door Performance		
Operation / Style	Structural Rating	U-Value Range
Single Panel	R-50 / LC-50	0.27 - 0.31
Two Panel - French	R-50 / LC-50	0.27 - 0.31
SDL Depth (Max Profile Height)		
Exterior	7/16"	
Interior	9/16"	

TimberLine W-Series Sliding Door Highlights, Performance and Operational Styles

- Architectural Grade Aluminum Frame
 - 5-5/8" Frame Depth
 - 4-9/16" and 6-9/16" Jamb Depths
- Thermally Broken Aluminum Frame and Patented SolidCore™ Thermal Barrier in Doors
- Corner Key Technology for Maximum Structural Performance
- Stainless Steel Quad Precision Bearing Roller System
- Butt Joint Panels & Extruded Fin
- Internal or Simulated Divided Light (SDLs) Grids Available
- Pine Interior
- High-Performance 2604 and 2605 Powder Finishes
- Custom Color Matching and Heat Reflective Paint Options

Sliding Door Sizing (W200S)					
Operation	Width		Height		Max UI
	Min	Max	Min	Max	
Two Panel	60"	168"	78"	144"	264"
Four Panel	120"	240"	78"	144"	408"
Sidelight - Narrow	12"	108"	78"	143-7/8"	191"
Sidelight - Fixed Panel	24"	108"	78"	144"	191"
Transom	12"	120"	12"	108"	191"

Sliding Door Performance		
Operation / Style	Structural Rating	U-Value Range
Two Panel	R-50 / LC-50	0.26 - 0.31
Four Panel	R-50 / LC-50	0.26 - 0.31
SDL Depth (Max Profile Height)		
Exterior	7/16"	
Interior	9/16"	



Quaker Window Products
 504 U.S. Hwy 63 South
 Freeburg, MO 65035
 (800) 347-0438
www.quartzluxurywindows.com

Discover More Here :



QTZ-TL WD 0525

The products described above are protected by one or more patents. Please refer to www.quakerwindows.com/patent-information for more information.