



TimberLine W-Series Doors (W200)

TimberLine W-Series Doors have been designed to open and elevate the visual appeal of your home's natural elegance and span the divide between the outside and inside.

By infusing an architectural aluminum frame with a natural wood pine interior, the W-Series Collection offers the chance to customize your living space and visually share the timeless comfort seen throughout the broad spectrum of modern home design.

This innovative collection incorporates industry leading SolidCore™ Technology which integrates Azo-Core high density foam that acts as an insulator, allowing for superior energy performance. SolidCore™ was engineered to enhance the natural charm of your home's unique style regardless of region or climate.



Available in Swing or Sliding operational styles along with sidelites, transoms and multiple mulling configurations.



TimberLine W-Series Swing Door (W200I/W200O) Highlights, Performance and Operations

- Architectural Grade Aluminum Frame
 - 5-5/8" Frame Depth
 - 4-9/16" and 6-9/16" Jamb Depths
- Thermally Broken Aluminum Frame and OptiCore® Panels
- SolidCore™ Thermal Barrier in Doors
- Pine Interior
- Corner Key Technology for Maximum Structural Performance
- Adjustable Butt Hinges Offer Multi-Directional Adjustment
- Butt Joint Panels
- Wide and Narrow Panel Options
- Available as Inswing (W200I) or Outswing (W200O)
- Raised Profile and Applied Grid Capabilities
- Standard, ADA, and No Sill Options
- High-Performance 2604 and 2605 Powder and Class 1 Anodized Finishes
- Custom Color Matching and Heat Reflective Paint Options

Swing Door Sizing					
Operation	Width		Height		Max UI
	Min	Max	Min	Max	
Single Panel	24"	48"	78"	144"	180"
Two Panel - French	48"	96"	78"	144"	216"
Sidelight - Narrow	15"	108"	78"	143-7/8"	191"
Sidelight - Fixed Panel Set	24"	108"	78"	144"	191"
Transom	12"	120"	12"	108"	191"

Swing Door Performance		
Operation / Style	Structural Rating	U-Value Range
Single Panel	R-50 / LC-50	0.24 - 0.29
Two Panel - French	R-50 / LC-50	0.24 - 0.29
SDL Depth (Max Profile Height)		
Exterior	7/16"	
Interior	9/16"	

TimberLine W-Series Sliding Door (W200S) Highlights, Performance and Operations

- Architectural Grade Aluminum Frame
 - 5-5/8" Frame Depth
 - 4-9/16" and 6-9/16" Jamb Depths
- Thermally Broken Aluminum Frame and OptiCore® Panels
- SolidCore™ Thermal Barrier in Doors
- Pine Interior
- Corner Key Technology for Maximum Structural Performance
- Stainless Steel Quad Precision Bearing Roller System
- Butt Joint Panels
- Extruded Fin
- Raised Profile and Applied Grid Capabilities
- High-Performance 2604 and 2605 Powder and Class 1 Anodized Finishes
- Custom Color Matching and Heat Reflective Paint Options

Sliding Door Sizing					
Operation	Width		Height		Max UI
	Min	Max	Min	Max	
Two Panel	60"	168"	78"	144"	264"
Four Panel	120"	240"	78"	144"	408"
Sidelight - Narrow	12"	108"	78"	143-7/8"	191"
Sidelight - Fixed Panel	24"	108"	78"	144"	191"
Transom	12"	120"	12"	108"	191"

Sliding Door Performance		
Operation / Style	Structural Rating	U-Value Range
Two Panel	R-50 / LC-50	0.26 - 0.31
Four Panel	R-50 / LC-50	0.26 - 0.31
SDL Depth (Max Profile Height)		
Exterior	7/16"	
Interior	9/16"	



Quaker Window Products
 504 U.S. Hwy 63 South
 Freeburg, MO 65035
 (800) 347-0438
www.quartzluxurywindows.com

Discover More Here :

